

NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.


MIL-PRF-39016/24E
20 JULY 1988
SUPERSEDING
MIL-R-39016/24D
10 February 1984

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, SPDT, LOW LEVEL
TO 1.0 AMPERE WITH INTERNAL DIODES FOR COIL TRANSIENT
SUPPRESSION AND POLARITY REVERSAL PROTECTION

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this
specification and the latest issue of MIL-R-39016.



Inches	mm	Inches	mm	Inches	mm
.001	0.03	.031	0.79	.280	7.11
.002	0.05	.035	0.89	.335	8.51
.003	0.08	.200	5.09	.370	9.40
.017	0.43	.275	6.99		

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is $\pm .010$ (0.25 mm).
4. Terminal numbers shown above are for reference only. Numbers do not appear on the relay.
5. Relays shall have a plus (+) sign placed on the circuit diagram as shown.
6. All leads shall be electrically insulated from the case.
7. Coil symbol optional in accordance with MIL-STD-1285.
8. Circuit diagram shown on part is the terminal view.

FIGURE 1 Dimensions and configuration.


(E) denotes changes

AMSC N/A


1 of 8

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5945



Inches	mm
.001	0.03
.002	0.05
.003	0.08
.012	0.30
.016	0.41
.017	0.43
.031	0.79
.035	0.89
.100	2.54
.150	3.81
.200	5.08
.275	6.99
.300	7.62
.335	8.51
.370	9.40
.398	10.11



NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± 0.010 (0.25 mm).
- ④ 4. Spreader pads shall be certified to MIL-M-38527, M38527/05-004.
5. Dimensions and tolerance shown for the bottom view of the spreader pad are for the center to center locations of the holes in the spreader pad.
6. Shape optional within the envelope dimension.
7. Terminal numbers shown above for reference only. Numbers do not appear on relay.
8. Relays shall have a (+) sign placed on circuit diagram as shown.
9. All leads shall be electrically insulated from the case.
10. Circuit diagram shown on part is the terminal view.
11. Terminal numbers shown above for reference only. Numbers do not appear on relay.

FIGURE 2. Dimensions and configuration relay with spreader pad attached.

REQUIREMENTS:

CONTACT DATA:

Load ratings:

High level (relay case grounded):

Resistive:

1.0 ampere at 28 V dc.

500 milliamperes at 115 V ac 400 Hz case not grounded.

250 milliamperes at 115 V ac 60 Hz case not grounded.

100 milliamperes at 115 V ac 60 and 400 Hz case grounded.

Inductive load: 0.2 ampere at 28 V dc with 0.32 henry inductance.

Lamp: 0.10 ampere at 28 V dc.

Low level: 10 to 50 μ A at 10 to 50 mV dc or peak ac.

Intermediate current: Applicable.

Contact resistance or voltage drop:

(E) Initial: 0.10 ohm maximum (0.125 maximum with spreader pad attached).

High level:

During life: Not more than 5 percent of open circuit voltage.

After life: 0.20 ohm maximum (0.225 ohm maximum with spreader pad attached).

Low level:

During life: 33 ohms maximum.

After life: 0.15 ohm maximum (0.175 ohm maximum with spreader pad attached).

Intermediate current:

During: 1 ohm maximum.

After: 0.20 ohm maximum (0.225 ohm maximum with spreader pad attached).

Contact bounce: 1.5 milliseconds maximum (applicable to failure rate level "L").

Contact stabilization time: 2.0 milliseconds maximum (applicable to failure rate levels "M", "P", and "R").

Overload (high level only): Two times rated current.

COIL DATA: See table I.

Operate time: 2.0 ms maximum over temperature range with rated coil voltage.

Release time: 4.0 ms maximum over temperature range from rated coil voltage.

MIL-R-39016/24E

ELECTRICAL DATA:

Insulation resistance: 1/ 10,000 megohms minimum at 500 Vdc, except the resistance between coil and case at high temperature shall be 1,000 megohms minimum.

Dielectric withstanding voltage: 1/

	Sea level V rms (60 Hz)	Altitude V rms (60 Hz)
Between case, frame, or enclosure and all contacts both in the energized and deenergized positions - -	500	300 All terminals to case
Between case, frame, or enclosure and coil - - - - -	500	
Between all contacts and coil - - - - -	500	
Between open contacts in the energized and deenergized positions - - - - -	500	
Between contact poles - - - - -	---	
Between coils of dual coil relays - - - - -	---	

DIODE CHARACTERISTICS:

- Ⓔ Coil transient suppression: Applicable.
- Ⓔ Diode breakdown and block integrity (delete coil resistance and substitute the test in all inspection tables of MIL-R-39016):
- Ⓔ With applicable voltage applied to the relay coil circuit in the reverse direction, monitor leakage current with dc microammeter or oscilloscope or qualifying activity approved test equipment. Leakage current shall not exceed the specified value.

Maximum transient voltage: 1 volt.

- Ⓔ Breakdown voltage: 100 V dc minimum at 10 microamperes (μ A).

Maximum leakage current: 1 μ A at 50 V dc.

- Ⓔ Semiconductor in-process screening: Applicable, visual inspection of semiconductors shall be in accordance with MIL-STD-750, method 2073 or 2074.

ENVIRONMENTAL DATA:

Temperature range: -65°C to +125°C.

- Ⓔ Vibration (sinusoidal): MIL-STD-202, method 204, contact chatter shall not exceed 10 microseconds maximum for closed contacts, and 1 microsecond maximum closure for open contacts.
- Ⓔ Vibration (random): MIL-STD-202, method 214, test condition IG. Contact chatter shall not exceed 10 microseconds maximum for closed contacts, and 1 microsecond maximum closure for open contacts (applicable to qualification and group C testing only).
- Ⓔ Shock (specified pulse): MIL-STD-202, method 213, test condition B (75 g's). Contact chatter shall not exceed 10 microseconds maximum for closed contacts, and 1 microsecond maximum closure for open contacts.

Magnetic interference: Applicable.

Resistance to soldering heat: Applicable.

Acceleration: Applicable.

Salt atmosphere (corrosion): In accordance with MIL-STD-750, method 1041.

1/ Insulation resistance and dielectric withstanding voltage tests must always precede all other specified electrical measurements. Connect all coil terminals together to avoid damage to diodes.

PHYSICAL DATA:

Terminal strength, MIL-STD-202, method 211:

Pull test: Test condition A, 1 pound pull.

Bend test: Test condition C, 1/2 pound load.

(E) Twist test: As specified in MIL-R-39016.

Solderability: Applicable.

Dimensions and configuration: See figures 1 and 2.

Weight: 2.27 grams (0.08 ounce) maximum, 2.52 grams (0.089 ounce) maximum with spreader pads attached.

Seal: Hermetic.

(E) Minimum marking: Military part number, "J" with the date code (example J8530), circuit diagram, manufacturer's name or source code.

LIFE TEST REQUIREMENTS:

High level: 100,000 cycles per relay.

(E) Low level: 100,000 cycles plus 900,000 cycles mechanical life.

PART NUMBER: M39016/24- (dash number from table I and suffix letter designating failure rate level).

(E) TABLE I. Dash numbers and characteristics. 1/

Dash numbers 2/				At 25°C								Over temperature range		
Lead length	Lead length	Lead length	Spreader pads	Coil voltage		Coil resist-	Coil circuit		Speci-	Speci-	Speci-	Speci-	Speci-	Speci-
1.500	.187	.500	(fig. 2)	(V dc)		ance	current		fied	fied	fied	fied	fied	fied
min	+ .010	min	4/	5/		(ref. only)	6/ (mA)		pickup	hold	drop-	pickup	hold	drop-
3/						Ohms	Max	Min	(volt- age)	(volt- age)	(volt- age)	(volt- age)	(volt- age)	(volt- age)
				Rated	Max				Max			Max		
013	019	025	031	5.0	6.0	50	100.0	72.7	3.5	1.7	0.23	4.5	2.4	0.15
014	020	026	032	6.0	8.0	98	62.4	46.3	4.1	2.0	0.28	5.5	2.8	0.18
015	021	027	033	9.0	12	280	33.7	25.9	6.3	3.0	0.54	7.8	4.2	0.35
016	022	028	034	12	16	500	25.6	20.0	8.0	4.0	0.63	10	5.6	0.40
017	023	029	035	18	24	1,130	17.2	13.6	11.6	6.0	0.91	14.5	8.4	0.58
018	024	030	036	26.5	32	2,000	14.4	11.5	15.4	8.0	1.37	19	10.4	0.89

1/ Each relay possesses high level and low level capabilities. However, relays previously tested or used above 10 mA resistive at 6 V dc maximum or peak ac open circuits not recommended for subsequent use in low level applications.

2/ The suffix letter L, M, P, or R to designate the applicable failure rate level shall be added to the applicable listed dash number. Failure rate level (percent per 10,000 cycles): L, 3.0; M, 1.0; P, 0.1; R, 0.01. Example, 013L - - - - 036R.

3/ 1.500 leads are inactive for new design.

4/ Relays supplied with spreader pads (-031 through -036) shall have the pad rigidly attached.

5/ CAUTION: The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.

6/ Coil resistance not directly measurable at relay terminals. When rated voltage is applied to the coil terminals, the coil circuit current must be within the limits shown. Measure at 25°C at nominal voltage for 5 seconds, maximum.

QUALIFICATION INSPECTION:

Qualification inspection and sample size: See table II.

⑤ TABLE II. Qualification inspection and sample size. 1/

Single submission		Group submission
18 units plus 1 open unit for level L at C = 0 2/	M39016/24-030	18 units plus 1 open unit for level L at C = 0 2/
33 units plus 1 open unit for level M at C = 0 2/		33 units plus 1 open unit for level M at C = 0 2/
Qualification inspection as applicable		Qualification inspection as applicable
	M39016/24-025	2 units each part number
	M39016/24-026	qualification inspection
	M39016/24-027	table, group II
	M39016/24-028	
	M39016/24-029	

- 1/ For retention of qualification or extension of qualification to lower failure rate levels, all life test data accumulated on MIL-R-39016/20 and MIL-R-39016/21 may be used in addition to MIL-R-39016/24 data. Prior to performance of retention of qualification testing, the relay manufacturer shall preselect the sampling plan.
- 2/ The number of units required for qualification testing shall be increased as required in group V, table II, MIL-R-39016, if the relay manufacturer elects to test the number of units permitting one or more failures. Prior to performance of qualification inspection, the relay manufacturer shall preselect the sampling plan.

Initial qualification of relays supplied with spreader pads (-031 through -036), shall be tested as specified below:

Perform the following tests as specified in the qualification inspection table of MIL-R-39016, in the order shown below:

- ⑤ Before installation of pad, screening, visual and mechanical examination (internal), thermal shock, resistance to solvents, vibration (sinusoidal), vibration (random), shock (specified pulse), acceleration, terminal strength, magnetic interference (when specified), capacitance (when specified), coil life (applicable to continuous duty relays only), resistance to soldering heat, salt spray (corrosion), overload (applicable to high level relays only), life, terminal strength, and intermediate current.

After installation of pad perform the following tests as specified in the qualification inspection table of MIL-R-39016, in the order shown below:

- ⑤ Insulation resistance, dielectric withstanding voltage, static contact resistance, specified pickup, hold, and dropout values (voltages), coil resistance, operate and release time, contact dynamic characteristics, coil transient suppression (when specified), solderability, seal, visual and mechanical inspection (external).

Qualification inspection (reduced testing for previously qualified relays) for relays supplied with spreader pads (-031 through -036), two (2) units of the 26.5 volt rated coil voltage (-036) shall be tested as specified below:

Before installation of pad perform the following tests as specified in the qualification inspection table of MIL-R-39016 in the order shown below:

For failure rate level L only: Screening.

- ⑤ For failure rate levels M, P, and R: Vibration (sinusoidal) test duration shall be 10 minutes, vibration (random), particle impact noise detection (P.I.N.D., when specified), screening.

MIL-R-39016/24E

After installation of pad perform the following tests as specified in the qualification inspection table of MIL-R-39016 in the order shown below:

- (E) Insulation resistance, dielectric withstanding voltage, static contact resistance; specified pickup, hold, and dropout values (voltages), coil resistance, operate and release time, contact dynamic characteristics, coil transient suppression (when specified), solderability, seal, visual and mechanical inspection (external).

Group A testing for relays supplied with spread pads (-031 through -036), shall be tested as specified below:

- (E) Before installation of pad perform subgroup 2 of group A tests.
- (E) After installation of pad perform subgroups 3 and 4 of group A tests.

Qualification inspection (reduced testing) and sample size: See table III.

If the relays produced for MIL-R-39016/24 are similar in construction and design except for the diodes, coils, and headers, as applicable, to the relays produced for MIL-R-39016/20, or MIL-R-39016/21, then reduced testing for qualification of MIL-R-39016/24 relays may be performed concurrent with or subsequent to successful qualification of MIL R 39016/20 or MIL-R-39016/21.

(E) TABLE III. Qualification inspection (reduced testing).

Examination or test
2 units each coil voltage Group II of qualification inspection table 1 unsealed sample unit for internal examination

SUPERSESSION DATA:

Supersession data: See table IV.

TABLE IV. Supersession data. 1/

Superseded part no. M39016/24-	New part no. M39016/24-	Superseded part no. M39016/24-	New part no. M39016/24-
001	013	007	019
002	014	008	020
003	015	009	021
004	016	010	022
005	017	011	023
006	018	012	024

1/ Dash numbers -013 through -018 are inactive for new design and are for support of existing equipment designs only.

Cross reference for Government logistical support: See table V.

TABLE V. Cross reference for Government logistical support.

Superseded part number M39016/24-	New part number M39016/24-	Support with part number M39016/24-	New part number M39016/24-	Support with part number M39016/24-
001	013	013	025	025
002	014	014	026	026
003	015	015	027	027
004	016	016	028	028
005	017	017	029	029
006	018	018	030	030
007	019	025	031	031
008	020	026	032	032
009	021	027	033	033
010	022	028	034	034
011	023	029	035	035
012	024	030	036	036

CONCLUDING MATERIAL

Custodians:

Army - ER
Navy - EC
(E) Air Force - 85

Review activities:

Army - AR
(E) Navy - AS, OS, SH
Air Force - 99
DLA - ES

User activities:

(E) Navy - MC
Air Force - 11

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0757-18)